



**NOTES:**

- A. NO NATIVE MATERIAL WITHIN 24" OF A.C. COURSE. USE 3/4" CLASS II A.B. WHERE PIPE ZONE IS WITHIN 48" OF A.C. COURSE.
- B. ADDITIONAL GRINDING AND PAVING MAY BE REQUIRED IF EXISTING SURFACE CRACKING IS WITHIN TWO (2) FEET OF EXISTING PAVEMENT EDGE OR A LOCATION WITH AN EXISTING UNSUITABLE EDGE TO PAVE AGAINST. FINAL GRIND AREA WILL BE SET AT THE INSPECTOR'S DISCRETION. ADDITIONAL GRINDING AND PAVING WORK SHALL BE AT THE CONTRACTOR'S EXPENSE.
- C. SAWCUT PAVEMENT PRIOR TO TRENCH EXCAVATION. SAWCUT EDGE IS ONE HALF DISTANCE BETWEEN TRENCH AND EDGE OF GRIND.

**THE CITY OF WEST SACRAMENTO - STANDARD DETAIL**



APPROVED: Aug. X, 2025

STANDARD  
DETAIL #

**113**

TITLE:

**TRENCH RESURFACING  
WHEN FABRIC  
IS REQUIRED**

