



**PATH CROSS SECTION**



**HEADER BOARD SPLICE PLAN VIEW**



**HEADER BOARD SPLICE**

①	3 INCH THICK HMA PAVEMENT
②	2" x 4" WOOD HEADER BOARDS
③	2" x 4" x 18" WOOD STAKE, 4' O.C.
④	MINIMUM 6 INCH CLASS II (3/4 MAX.) OVER 6 INCH SUBGRADE OR, IF REQUIRED, CLASS II (3/4" MAX.) ASB, UNLESS OTHERWISE SHOWN ON THE APPROVED PLANS OR DETAILED IN THE PROJECT SOILS REPORT. ALL MATERIALS SHALL BE PROCESSED TO 95% RELATIVE COMPACTION.
⑤	2" X 4" X 24" WOOD SPLICE
⑥	20 PENNY NAILS, GALVANIZED (TYPICAL ALL NAILS, 4 NAILS PER STAKE AND 4 NAILS AT HEADER BOARD SPLICE, AS SHOWN).

**NOTES:**

- A. HMA PAVEMENT SHALL BE CONSTRUCTED IN ACCORDANCE WITH CITY STANDARD CONSTRUCTION SPECIFICATIONS SECTION 8 AND STATE STANDARD SPECIFICATIONS 39. HMA PAVEMENT SHALL BE 3/8 - INCH TYPE A HMA AGGREGATE GRADATION WITH PG 64-10 GRADE ASPHALT BINDER.
- B. ALL WOOD SHALL BE PRESSURE TREATED DOUGLAS FIR OR HEM-FIR UNLESS OTHERWISE SPECIFIED.

**THE CITY OF WEST SACRAMENTO - STANDARD DETAIL**



APPROVED: Aug. X, 2025

STANDARD  
DETAIL #  
**213**

TITLE:  
**ASPHALT  
CONCRETE PATH**

