



①	G5-05 CHRISTY BOX OR APPROVED EQUAL. LID SHALL BE ENTITLED "MONUMENT".
②	2½" DIAMETER, SURVEY MARKER SHALL BE LIETZ 8134-16, OR SERVICE COMPANY 287-C. GEODETIC BRASS CAPS SHALL BE ¾" DIAMETER STAMPED "CITY OF WEST SACRAMENTO" AND "GEODETIC CONTROL SURVEY", OR AS REQUIRED BY CITY ENGINEER.
③	EXISTING GRADE.
④	4,000 PSI MIN CONCRETE. ALL EXPOSED CONCRETE EDGES SHALL HAVE A ½" RADIUS.
⑤	¼" DIAMETER WELDED STEEL CIRCULAR PLATE, ⅛" MAXIMUM LIP.
⑥	4" DIAMETER, 6 FEET LONG SCHEDULE 40 GALVANIZED PIPE.
⑦	¾" DIAMETER, 10 INCH LONG GALVANIZED ROD WELDED TO BOLLARD.

NOTES:

- A. THE R.C.E. OR L.S. NUMBER MUST APPEAR ON MONUMENT MARKERS.
- B. MARK REFERENCE POINT WITH A PUNCHMARK.
- C. BOLLARD SHALL BE PRIMERED & PAINTED WITH 2 COATS OF WHITE PAINT.
- D. BOLLARD TO BE INSTALLED IN UNIMPROVED AREAS.

THE CITY OF WEST SACRAMENTO - STANDARD DETAIL



APPROVED: Aug. X, 2025

STANDARD
DETAIL #
244

TITLE:
**SURVEY MONUMENT
OUTSIDE OF
ROADWAY**

